

- Converts rust to form a matte black durable finish.
- Eliminates the need for scraping, sandblasting or priming rusty surfaces.
- Prevents further rusting on surfaces exposed to rain, sun and salt spray.
- Top coat with an industrial grade paint for ultimate durability and protection.

When applied to any rusty surface, **United 103 SPRAY TRIUMPH** will quickly and easily convert the residual rust to a black protective polymeric coating. This inert protective coating prevents further rusting and corrosion.

DIRECTIONS:

1. For best results, use when can is between 50°F and 90°F (10°C and 32°C).
2. Shake can at least one minute after rattle is heard and occasionally during use.
3. Use a wire brush or sandpaper to remove as much loose and flaky rust as possible.
4. Spray surface with steady even strokes at a distance of 8 to 12 inches. A chemical reaction will cause the rust to turn black. Allow 24 hours before applying a second coat or when topcoating with a different coating.
5. If clogging develops, turn sprayhead ¼ turn or remove and clean sprayhead slot. DO NOT stick pin or other objects into can opening. With can and sprayhead pointed away from you, reinsert sprayhead with a gentle twisting motion.
6. To clear sprayhead for future use, turn can upside down and spray for 3 seconds. Completely empty cans may be recycled or disposed of with regular trash. Dispose partially empty cans responsibly. DO NOT incinerate or compact.

KEEP OUT OF REACH OF CHILDREN.

An SDS for this product is available on United's website. Please read the SDS carefully and follow all directions when using or handling this product.



Made in USA

1223

UNITED

LABORATORIES

United 103 SPRAY TRIUMPH Rust Converter and Primer Coat

DANGER

EXTREMELY FLAMMABLE LIQUID AND VAPOR. VAPORS MAY CAUSE FLASH FIRE. CONTENTS UNDER PRESSURE. VAPOR HARMFUL.

KEEP OUT OF REACH OF CHILDREN.

See other cautions on back panel.

NET WT. 12 OZ. (340 grams)

PRECAUCION AL USUARIO:

Si usted no puede leer Ingles, pregunte a alguien que le traduzca esta etiqueta para usted antes de uso.

Sold By:

UNITED LABORATORIES, INC.
320 37th Avenue • St. Charles, IL 60174
1-800-323-2594 • www.unitedlabsinc.com

DANGER: Extremely flammable aerosol. Contains gas under pressure; may explode if heated. Causes serious eye irritation. May cause an allergic skin reaction. May cause drowsiness or dizziness. May cause damage to organs through prolonged or repeated exposure.



Prevention: Pressurized container: do not pierce or burn, even after use. Use only with adequate ventilation. Do not breathe dust/vapors/spray mist. Avoid contact with eyes/skin/clothing. Wear protective gloves/clothing/glasses. Keep away from heat/sparks/open flames/hot surfaces. Do not eat/drink/smoke when using this product. Do not spray on naked flame or other ignition sources. **Response:** In case of fire, use extinguishing powder or water spray. Immediately contact a doctor or POISON CONTROL CENTER if you feel unwell. If medical attention is needed, have product label at hand. **IF IN EYES:** Rinse with water for several minutes. Remove contact lenses if present. If eye irritation persists seek medical attention. **IF SWALLOWED:** Rinse mouth with water. Do not induce vomiting. **IF INHALED:** Remove to fresh air. **IF ON SKIN:** Wash thoroughly with water. Remove all contaminated clothing. **Storage:** Store locked up. Protect from sunlight and do not expose to temperatures exceeding 50°C/122°F. **Disposal:** Dispose of product in accordance with local/regional/national/international regulations. **Additional Precaution Statements:** Vapors may ignite explosively and cause a flash fire. Prevent buildup of vapors by opening windows and doors to achieve cross ventilation. Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately inhaling the contents may be harmful or fatal. In cases where short and/or long term overexposure conditions exist, a charcoal filter respirator should be worn. Follow respirator manufacturer's directions for use.

CONTAINS (CAS#): Acetone (67-64-1), Propane (74-98-6), Tert-Butyl Acetate (540-88-5), Talc (14807-96-6), N-Butane (106-97-8), Diacetone Alcohol (123-42-2), Propylene Glycol (57-55-6), VM&P Naptha (64742-89-8), Methyl Isobutyl Ketone (108-10-1), Methyl Propyl Ketone (107-87-9), PM Acetate (108-65-6). **OTHER INGREDIENTS:** "Contents Partially Unknown", Soya Alkyd Resin.

WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov.