

United 123 SPRAY TRIUMPH Red Primer Coat is a fast drying surface sealer that provides maximum rust protection and better adhesion for a finishing top coat.

BENEFITS:

VOC compliant • Fast dry, Sag free
Provides maximum rust or corrosion protection
Excellent adhesion • Minimum overspray
Single coat hiding • Effective against rust and chemicals

FOR USE ON:

Bare metal or wood • Structural steel • Machinery
Farm Equipment • Steel window frames • Lawn furniture

DIRECTIONS

1. For best results prepare surface by brushing the rust from the surface using a wire brush or sand paper. Clean the surface to remove grease and grime. Surface must be clean, dry and free of rust before applying Red Primer Coat. Protect surrounding areas from spray mist. For best results, use when can is between 50°F and 90°F (10°C and 32°C).
2. Shake can at least one minute after rattle is heard and occasionally during use.
3. Spray surface with steady even strokes at a distance of 8 to 10 inches (20 to 25cm). Several light coats give a better finish than one heavy coat.
4. If clogging develops, turn sprayhead 1/4 turn or remove and clean sprayhead slot. Do not stick pin or other objects into can opening. With can and sprayhead pointed away from you, reinsert sprayhead with a gentle twisting motion.
5. To clear sprayhead for future use, turn can upside down and spray for 3 seconds. Completely empty cans may be recycled or disposed of with regular trash. Dispose of partially empty cans responsibly. DO NOT incinerate or compact.

DRY TIME*:

To touch	5 minutes
To topcoat	30 minutes

*Curing/Recoat time is extended with multiple coats and excessively thick coats

CONTAINS:

Acetone 67-64-1, Propane 74-98-6, N-Butane 106-97-8, VM&P Naphtha 64742-89-8, Red Iron Oxide 1309-37-1, Ethyl Alcohol 64-17-5, Xylene 1330-20-7, Talc 14807-96-6, N-Butyl Acetate 123-86-4, Mineral Spirits 64742-48-7, Isobutyl Acetate 110-19-0, PM Acetate 108-65-6. OTHER INGREDIENTS: "Contents Partially Unknown", Phenolic-Insseed Alkyd Resin 68122-96-3.

WARNING: This product contains a chemical known to the State of California to cause cancer, birth defects or other reproductive harm. Primer Coatings Does Not Exceed 60% VOC or 1.20 MIR



United 123 SPRAY TRIUMPH Red Primer Coat

DANGER
EXTREMELY FLAMMABLE LIQUID AND VAPOR. VAPORS MAY CAUSE FLASH FIRE. CONTENTS UNDER PRESSURE. VAPOR HARMFUL.

KEEP OUT OF REACH OF CHILDREN.

See other cautions on back panel.

NET WT. 12 OZ. (340 grams)

PRECAUCION AL USUARIO:

Si usted no puede leer Ingles, pregunte a alguien que le traduzca esta etiqueta para usted antes de uso.

Sold By:

UNITED LABORATORIES, INC.
320 37th Avenue • St. Charles, IL 60174
1-800-323-2594 • www.unitedlabsinc.com

DANGER Extremely flammable aerosol. Contains gas under pressure; may explode if heated. Causes skin irritation. Causes serious eye irritation. Suspected of causing cancer. Suspected of damaging fertility or the unborn child. May cause drowsiness or dizziness. May cause damage to organs through prolonged or repeated exposure.



Prevention: Pressurized container: do not pierce or burn, even after use. Use only with adequate ventilation. Do not breathe dust/vapors/spray mist. Avoid contact with eyes/skin/clothing. Wear protective gloves/clothing/glasses. Keep away from heat/sparks/open flames/hot surfaces. Do not eat/drink/smoke when using this product. Do not spray on naked flame or other ignition sources.

Response: In case of fire, use extinguishing powder or water spray. Immediately contact a doctor or POISON CONTROL CENTER if you feel unwell. If medical attention is needed, have product label at hand. **IF IN EYES:** Rinse with water for several minutes. Remove contact lenses if present. If eye irritation persists seek medical attention. **IF SWALLOWED:** Rinse mouth with water. Do not induce vomiting. **IF INHALED:** Remove to fresh air. **IF ON SKIN:** Wash thoroughly with water. Remove all contaminated clothing. **Storage:** Store locked up. Protect from sunlight and do not expose to temperatures exceeding 50°C/122°F. **Disposal:** Dispose of product in accordance with local/regional/national/international regulations.

Additional Precaution Statements: Vapors may ignite explosively and cause a flash fire. Prevent buildup of vapors by opening windows and doors to achieve cross ventilation. Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately inhaling the contents may be harmful or fatal. In cases where short and/or long term overexposure conditions exist, a charcoal filter respirator should be worn. Follow respirator manufacturer's directions for use.

KEEP OUT OF REACH OF CHILDREN.

An SDS for this product is available through United's website, www.unitedlabsinc.com, providing 24 hour access. Please read the SDS carefully and follow all directions when using or handling this product.



Manufactured and Printed in U.S.A.

1015